

SECTION 12

Water Softeners

12

DELTA IKARIA

Hot Water Softener

Standard Features:

- Ultra Compact
- Easy to Install
- Easy to Use
- No Power Required
- Automatic Demand Based Regeneration
- Uses Less Water
- Uses Less Salt
- Bypass Valve
- Maximum Temperature 65°C
- 2 Year Warranty*



The DELTA IKARIA water softener can soften up to 750L per hour of hot water at a maximum temperature of 65°C.
Regenerating automatically as required the DELTA IKARIA regenerates in just 15 minutes, using only 18L of water and 0.3kgs of salt.

Models:

Model	Flow Rate l/h	Connections inch	Capacity ppm/m3	Operating Range PPM
IKARIA	750	3/4	150	200 - 600

Dimensions:

241mm (W) x 538mm (L) x 480mm (H)

Applications:

For commercial coffee machines, dishwashers, bakery ovens, steamers, hot water dispensers, reverse osmosis appliances, vending machines.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.

SECTION 12

Water Softeners

DELTA IKARIA DUPLEX

Hot Water Softener

12

Standard Features:

- Ultra Compact
- Easy to Install
- Easy to Use
- No Power Required
- Automatic Demand Based Regeneration
- Duplex Model Provides Continuous Uninterrupted Soft Water
- Uses Less Water
- Uses Less Salt
- Bypass Valve
- Maximum Temperature 65°C
- 2 Year Warranty*



The DELTA IKARIA DUPLEX water softener can soften up to 1500L per hour of hot water at a maximum temperature of 65°C. Regenerating automatically as required the DELTA IKARIA DUPLEX regenerates in just 15 minutes, using 18L of water and 0.3kgs of salt.

Models:

Model	Flow Rate l/h	Connections inch	Capacity ppm/m3	Operating Range PPM
IKARIA DUPLEX	1500	3/4	2 x 150	200 - 600

Dimensions:

470mm (W) x 498mm (L) x 463mm (H)

Applications:

For commercial coffee machines, dishwashers, bakery ovens, steamers, hot water dispensers, reverse osmosis appliances, vending machines.

* Please refer to 'Aqua Products Limited' terms and conditions of sale for complete warranty conditions.